

Spreader Settings

| Product Name | Spreader (Make/Model) | Spread Width (m) | Disc/Vane Type | Spreader Height | Tilt (o) | PTO/Disc speed (rpm) | Vane setting / Drop on point / Discharge point | Application Rate(kg/ha) | Forward Speed (km/h) | % CV Achieved | |
|----------------------------|-----------------------------|------------------|-----------------|-----------------|----------|----------------------|--|-------------------------|----------------------|---------------|------|
| Borealis LAT Gran AN 33.5% | Amazone ZA-M Ultra | 24 | OM 24-48 | 80 | | 720 | 20/44 | 250 | 10 | 7.9 | |
| | | 36 | OM 24-48 | 80 | | 720 | 25/47 | 250 | 10 | 6.5 | |
| | | 30 | OM 24-48 | 80 | | 720 | 23/47 | 250 | 10 | 6.6 | |
| | | 42 | OM 24-48 | 90-96 | | 720 | 28/52 | 250 | 10 | 7 | |
| | KRM M2 base | 48 | OM 24-48 | 90-96 | | | 870 | 28/55 | 250 | 10 | 7.5 |
| | | 24 | E2T | | 75 | 2 | 540 | 1/2 | 250 | 10 | 8.3 |
| | | 30 | E6T | | 75 | 2 | 540 | 1/2 | 250 | 10 | 8.9 |
| | | 36 | E8T | | 75 | 2 | 540 | 1/2 | 250 | 10 | 7.8 |
| | Kuhn Axis 30.1 | 42 | E8T | | 85 | 4 | 650 | 2/3 | 250 | 10 | 7.1 |
| | | 24 | S4 | | 50 | | 540 | | 250 | 10 | 6.7 |
| | | 24 | s6 | | 50 | | 540 | | 250 | 10 | 8.6 |
| | | 30 | S6 | | 50 | | 600 | | 250 | 10 | 6.4 |
| | Kverneland Exacta HL | 36 | S8 | | 50 | | 540 | | 250 | 10 | 8.7 |
| | | 24 | 285/285/285 = S | | 75 | | 525 | | 250 | 10 | 7.5 |
| | | 30 | 285/285/285 = L | | 75 | | 525 | | 250 | 10 | 7.7 |
| | | 36 | Lift Vanes = I | | 75 | | 525 | | 250 | 10 | 7.4 |
| 27N 9 S03 | Amazone ZA-M Ultra | 48 | Lift Vanes = F | | 75 | 570 | | 250 | 10 | 13.5 | |
| | | 24 | OM 24-48 | 80 | | 720 | 17/47 | 250 | 10 | 7.4 | |
| | | 36 | OM 24-48 | 80 | | 720 | 21/52 | 250 | 10 | 7.6 | |
| | Kverneland Exacta HL | 48 | OM 24-48 | 90-96 | | | 800 | 28/55 | 250 | 10 | 10.6 |
| | | 24 | Lift Vanes = U | | 75 | | 465 | | 250 | 10 | 9.59 |
| | | 36 | Lift vanes = M | | 75 | | 525 | | 250 | 10 | 8.5 |
| | | 48 | Lift Vanes = K | | 75 | | 570 | | 250 | 10 | 9.32 |